

Our reputation is spreading

The Williams In-Line Effluent Filter is designed to ensure removal of debris that creates blockages in irrigation nozzles. Liquid flows through the screen inside the filter's body. It is a simple procedure to open the top of the filter, remove the filtering screen, discard the trapped debris, then replace the cleaned screen and reassemble the filter. This feature makes the cleaning process a simple and tidy operation.

FEATURES		
Galvanised or Stainless Screens come in:	76 hose / 64 BSP inlet and outlet	
37mm x 16mm Diamond Hole - Galvanised	Over centre lid catches for quick opening	
20mm x 12mm Diamond Hole - Galvanised	Bleed valve for auto draining of filter	
12mm x 6mm Diamond Hole - Galvanised	NZ Designed and Manufactured	
4mm Round Punched Hole - Galvanised	Neat and tidy, easy to use	
3mm Round Punched Hole - Stainless Steel	Built to last and cost effective	

Williams' In-Line Filters





TALK TO US ABOUT YOUR **EFFLUENT SPREADING** REQUIREMENTS AND WE CAN TAILOR MAKE A SYSTEM TO SUIT YOUR NEEDS














In-Line Filter Parts



F1637



F1220



F612



F4



F3SS



IN-LINE EFFLUENT FILTER 64MM BSP THREADS

COMPLETE FILTER & SCREEN		
PART	CODE	
16 x 37 Galv Screen	F1637	
12 x 20 Galv Screen	F1220	
6 x 12 Galv Screen	F612	
4mm Round Galv Screen	F4	
3mm Round Stainless Steel	F3SS	

FILTER SCREEN ONLY		
PART	CODE	
16 x 37 Galv Diamond Screen	FS1637	
12 x 20mm Diamond Hole, Galv	FS1220	
6 x 12 Diamond Hole, Galv	FS612	
4mm Round Punched Hole, Galv	FS4	
3mm Punched Hole, Stainless Steel	FS3SS	

Note: Filters have been designed and tested for 100psi, we do not recommend pressures higher than 100psi.