

Increase your pasture production by capitalizing on your farms available resources with the Williams Greenback Spider Travelling Irrigator. A simple speed change procedure with a choice of five travel speeds, allows for greater control of effluent application depths (minimum of 5mm) thus optimizing the benefits of the natural fertilizer.

FEATURES					
5mm application depth	Distribution uniformity of less than 1.25				
5 travel speeds	Suitable for electric and PTO pumps				
Even spread with new arm design	Travel distance up to 400 metres				
Available with multi strand galvanised, stainless steel or nylon	NZ Designed and Manufactured				
winch rope 250m, 300m or 400m of 5mm wire rope	Neat and tidy, easy to use				
Drags up to 90mm alkathene	Built to last				
Maximum volume of 90 cubic metres per hour	Cost effective				



# Williams' Greenback Spider

### PERFORMANCE CHART


	Pressure at Irrigator with 13mm nozzles								
	30psi		40psi		50psi				
u	Average Application Depth	Travel Speed Metres/Minutes	Average Application Depth	Travel Speed Metres/Minutes	Average Application Depth	Travel Speed Metres/Minutes			
revolution 7	35	0.30m / min	36	0.40m / min	39	0.40m / min			
a 4	17	0.60m / min	18	0.75m / min	20	0.80m / min			
ы <b>6</b>	13	1.05m / min	14	1.10m / min	15	1.20m / min			
<b>8</b> g	9	1.60m / min	9	1.65m / min	10	1.60m / min			
01 <sup>ta</sup>	5	2.00m / min	5	2.10m / min	6	2.20m / min			
Teeth taken per 0 8 9	Approx. Flowrate: 19,625 L/Hr Welted Diameter: 34 m		Approx. Flowrate: 25,755 L/Hr Welted Diameter: 38 m		Approx. Flowrate: 30,120 L/Hr Welted Diameter: 42 m				

\*Results from testing with Massey University. These tests have been done using liquid from an effluent pond to give the most accurate results possible. This information should only be used as a guideline.

#### **SPECIFICATIONS**

Suits 15hp - 30hp High Pressure Pumps & PTO Pumps							
Travel Distance	250 - 400m	Minimum Pressure	2 bar				
Spreading Width	30 - 50m	Maximum Pressure	6 bar				
Boom Width	9m	Max. Draghose	90 od				

## TALK TO US ABOUT YOUR **EFFLUENT SPREADING** REQUIREMENTS AND WE CAN TAILOR MAKE A SYSTEM TO SUIT YOUR NEEDS



#### WILLIAMS ENGINEERING 2011 LTD

🕙 Waitakaruru RD 6, 🛛

Thames 3576, New Zealand

07 867 3176 or 0800 4 EFFLUENT (0800 433 358)

07 867 3179